Certificate of Conformance

UE of Batch Release for sale in the EU

Product name, dose, dosage

Maxiva Panaxol CBD 25mg/ml

form and pack size:

Pharmaceutical Industries

Neuraxpharm Arzneimittel GmbH

:JueilD

Market:

Z4/209-MT

Germany

Batch number:

245 kits

Quantity

76/09/2024

Manufacturing Date:

07/2026 (Dev-0000019)

Expiry date:

CBD 2.6% (w/w)

Active Ingredient Concentration:

Charlotte Angel

Plant strain/s:

Deviations noted during manufacture:

✓ No Critical deviations

□ Critical deviations were reported and properly investigated and closed

The following document are attached-

- COA 24/209-MT
- Herbal Substance CoA 24/173-MT Strain Charlotte Angel
- Package COA
- o 10ml amber glass bottles batch number: 23/088-MT, 23/337-MT
- o 10ml amber glass bottles cap- batch number: 24/007-MT
- 1ml sterile graduated syringes for patient dosing: batch number: 24/104-MT
- o syringe cap- batch number: 22/148-MT
- o 30ml amber glass bottles batch number: 24/043-MT
- o 30ml amber glass bottles cap- batch number: 22/183-MT

Pharmaceutical Industries

And Just while

I hereby certify that all the manufacturing stages of this batch have been carried out in full compliance with EU GMP and the technical agreement in force. The herbal substance used for the production of the batch had not been irradiated during the growing of the product process. The batch is released for sale

by the undersigned Qualified Person in accordance with EC directive 2001/83.

Qualified Person: Signature & Date



Release COA for Std Cann Extract (CBD

Document Number: F-COA-009-DE 2.5% w.w) Naxiva Panaxol CBD 25mg/ml Document Version: 2.0 Effective Date: 29-Oct-2024

30 ml Effective Da Reference Specification Legacy number: F-COA-009-DE

Batch Details					
Batch number -Bulk oil	24/189-MT	Manufacturing date	26/09/2024		
Batch number - Finish product	24/209-MT	Expiry date	08/2026		

Test	Test Method	Specifications	Result
Identification		1	
TLC identification	SOP QC-179-MT/ VA1112 DAB [£]	Zonal pattern of test solution conforms to the zonal pattern of the reference solution	Complies
Organoleptic properties			
Appearance	SOP QC-136-MT Visual inspection DAB [£]	Homogenous greenish or yellow to brown liquid, no significant precipitate observed	Complies
Heavy metals ^{1,2}			
Cadmium	SOP 77405	≤ 1.0 ppm	< 0.05 ppm
Lead	ICP-MS	≤ 5.0 ppm	< 0.1 ppm
Mercury	—————————————————————————————————————	≤ 0.1 ppm	< 0.05 ppm
Physico-chemicals			
Relative density	SOP-183-MT / VA1044 Ph. Eur. 2.2.5 [◊]	Indicative	0.95
Water content	SOP-175-MT/ VA25322 Karl Fisher <i>Ph. Eur. 2.5.12</i> ^{\(\)}	≤0.5%	0.1%
Toxins- Mycotoxins			
Aflatoxin B1	SOP QC-131-MT /VA45110	≤ 2 μg/Kg	UQL
Total Aflatoxins (B1, B2, G1, G2)	Ph. Eur. 2.8.18 \(\)	≤ 4 μg/Kg	UQL
Ochratoxin A	SOP QC-322-MT /VA45118 <i>Ph. Eur.</i> 2.8.22 ^{\(\)}	≤18.85 μg/Kg	UQL
Microbiological Quality			
TAMC	MW024-01	≤ 10 ⁴ CFU/ml	< 10 CFU/ml
TYMC	Complies to Ph. Eur. 2.6.12 $^{\Diamond}$	≤ 10 ² CFU/mL	< 10 CFU/ml
Bile-tolerant gram- negative bacteria	MW024-01	< 10 ² CFU/ml	< 10 CFU/ml
E.Coli	Complies to Ph. Eur 2.6.31 \(\)	Absent in 1ml	Absent in 1 ml
Salmonella		Absent in 25 ml	Absent in 25 ml
Residual solvent			
Ethanol	QC-140-MT/ VA12301 GC-HS-FID	≤ 5000 ppm	NA
Assay - Cannabinoids co	oncentration (%w/w)		
CBN		≤ 2.5% m/m	0.01%
CBD	QC-181-MT	2.47% - 2.73% m/m (95-105 % from label claim)	2.64%
Δ9-ΤΗС	DAB [£]	$\leq 0.16\%$ m/m ($\leq 6\%$ from CBD label claim)	0.11%
Vitamin E	QC-149-MT / VA14060	≥ 0.4% m/m	0.4%
Pesticide Residue 1,2			<u>'</u>



Release COA for Std Cann Extract (CBD 2.5% w.w) Naxiva Panaxol CBD 25mg/ml

Document Number: F-COA-009-DE

Document Version: 2.0

		II LITECTIVE Date	. 23-061-2024
Pesticides	SOP 15005, 15010 LC-MS/MS, GC-MS/MS, Headspace-GC/MS Ph. Eur. 2.8.13 \(\)	Complies with the limits indicated in Ph. Eur.2.8.13	Complies

Aflatoxins UQL- Under quantification limit; LOQ Aflatoxin B1, B2, G1: 0,5 µg/kg; LOQ Aflatoxin G2: 1,0 µg/kg.

Ochratoxins UQL - Under quantification limit. The result of Ochratoxin A that is less than 0.5 µg/kg is reported UQL.

Residual Solvents UDL - Under detection limit. The result of Ethanol that is less than 170ppm is reported UDL.

Residual Solvents UQL - Under quantification limit. The result of Ethanol that is less than 500ppm is reported UQL.

Assay URL - Under reporting level. The concentration of THC and CBN that are less than 0.05% from the label amount of CBD are reported URL (0.001%)

⁶ Current version of monograph

Consecutive batch

- $^{\mathrm{f}}$ DAB Cannabis extractum normatum monograph
- 1. Performed by approved outsource laboratory
- 2. Pesticides and Heavy metals To be performed every 20th Batch. When skip lot testing is performed both results are reported from the Inflorescence COA.

Pesticides and Heavy metals testing required on Finished product:

3. Residual solvent - To be performed every 20th Batch.

number:					
1	☐ Yes; 🙀 No, results reported fro 24/173-MT		s. Batch no./s used during manu	facturing:	
		$\boxtimes PA$	SS 🗆 FAIL		
Approved by	Shani Bonan	Signature:	L	Date:	October 29, 2024
_	the review of the manufacturer Specifications and requirement		=		considered meeting/not meeting
QC Reviewed	l by:	Signature:		Date:	
	Chris Desira				October 29, 2024

REVISION HISTORY						
Date	Name of	Version no	Details of correction (including Chapter No)	Reason of correction		
	corrector					
12.03.2024	Shani	01	New Document	CCF-MT-2024-23		
	Bonan					
28/10/2024	Shani	02	Adding the method's number of QSI	1. CC-0000022		
	Bonan		2. Adding Residual solvent - To be performed every	2. CC-0000016		
			20th Batch			



Release COA for Std Cann Extract (CBD 2.5% w.w) Naxiva Panaxol CBD 25mg/ml 30 ml

Document Number: F-COA-009-DE

Document Version: 2.0 Effective Date: 29-Oct-2024

This is a representation of an electronic record that was signed electronically and this page is the manifestation of the electronic signatures.

Signatory Table

Action Name	User Name	Title	Signature Date
Send for Review (Written By)	Shani Bonan	QC Manager	28-Oct-2024 18:08
Send for Approval	Chris Desira	Head of Quality Assurance	29-Oct-2024 05:33
Review	Chris Desira	Head of Quality Assurance	29-Oct-2024 05:33
Approve	Chris Desira	Head of Quality Assurance	29-Oct-2024 05:34
Approve	Irene Zanetti	Qualified Person	29-Oct-2024 07:55
Approve	Shani Bonan	QC Manager	29-Oct-2024 11:50
QA Approval	Ivan Vidmar	Senior QA Specialist	29-Oct-2024 11:51

^{*} Dates are displayed according to the system time zone: (GMT+01:00) () (Europe/Malta)



Customer ...: PANAXIA PHARMACEUTICAL IND.

F.a.o.: QUALITY DEPARTMENT

Temse, 4/06/2021

CERTIFICATE OF CONFORMITY

This delivery contains the following articles :

Article Number	Quantity	Description + Item customer	Your ref.
T2133	50000	CAP	PO21000337 dd. 09/03/2021
		560 PP 099 WHITE	Our ref./Batch no
		CM-2054	21-0443/00

Approved by :

Patricia Raes

Dispatch department

Use-by date: 04/2024

We certify that the above components have been subject to in-process control and, if applicable, other testing. They comply with the agreed specification and were manufactured using the agreed materials, according a certified quality management system to ISO 9001:2015, EN ISO 13485:2016 and EN ISO 15378:2017.

Released by :

Nathalie Van Assche

QA department

Remy & Geiser GmbH PZ-FBL Band/Vol. Prüfzertifikat nach Fehlerbewertungsliste (Editio Cantor Verlag) Werk I / Plant I R&C 18.19.20.22.34 Remy & Gelser Str. 1 Test Certificate acc. to Defect Evaluation List aktuelle Ausgabe / current Ed. 98553 Hinternah Kunde: / customer: Panaxia Pharmaceutical DOSIERVERSCHLUSS / dosage closure Art.-Bez.: / article name: DOSIERVERSCHLUSSRSV 5,0 OVII /SPRITZEN-EINSATZNW18 W/TR 22126354 Ihre Auftr.-Nr.: PO22000312 Auftr.-Nr. LS-Nr.: 22248155 Stückzahl: 15000 Your order no.: Packing slip no.: Pieces supplied: ldent,-Nr. Ihre Ident.-Nr.: CM-2074 6615MA Chargen-Nr.: 111585 Stichprobe: 50 (315) Your article no.: quant. (qual) article on . Herstelldatum: 11/2020 Verfallsdatum: 5 date of manufacture: Ursprungsland: Deutschland Zchn-Nr.: 03006608-01 11/2025 Sterilisationsdatum: shelf life Country of origin: Germany drawing no.: entfällt Angaben zur Lagerung: Es bestehen keine besonderen Anforderungen an Temperatur und Luftfeuchtigkeit. Jedoch sind häufige, große Temperaturschwankungen zu vermeiden damit sich kein Kondenswasser bildet. Ferner sollte die Einwirkung von Temperaturen über 45°C vermieden werden um Verformungen auszuschließen. Storage conditions: There are no special requirements to temperature or humidity. However, high fluctuations in temperature have to be avoided, so that no condensation could be caused Furthermore, a temperature above 45°C should be avoided, to prevent distortion. Materialzusammensetzung: Einfärbung: RANDTROPFER-SCHRAUBKAPPERSK 5,0 OVI NW 18 W Purell ACP6541A (PEHD) DOSIERFILFESPRITZEN-EINSATZ NW 18 TR 1. Einzelteil: REMAFIN-EP-WEISS PL00075542-ZT component part 2. Einzelteil: component part Purell 1840H (PELD) 3. Einzelteil: 3. component part: 4. Einzelteil: #NV #NV ₩NV #NV #NV component part 5. Einzelteil: component part Stichprobenumfang nach Fehlerbewertungsliste (Quantitative Prūfung) QK Prüfvermerk: Entscheidung: + entspricht Sampling Inspection to defect Evaluation list (quantitative (tests) Insp. Remark Decision: + accepted Entscheidung ehler-Nr Fehler/Einzelmerkmal max.Fehter Defect/Individual chara Defects Decision Anllefening, Kennzeichnung, Verpackung / Delivery, labelling, packing Die Fehlermerkmale beziehen sich hier nicht auf das Packmittel selbst, sondern auf Paletten und Packeinheiten (Gebinde). Für die Prüfung dieser Fehlermerkmale ist ke Stichprobenverfahren anwendbar. Die Vergabe bezüglich dieser Merkmale ist eine fehlerfreie Lieferung. Fehlerklasse 1 bedeutet in diesem Zusammenhang, dass das Packmittel in der vorliegenden Anileferform nicht einsetzbar ist. Lässt sich die Ware mit geringem Aufwand durch Nachbesserung in einen verwendbaren Zustand bringen, so ist die The defect characteristics refer not to the packaging material itself but to the pallets and packaging units (containers). No random sampling method is applicable for the testing of these defect characteristics. The requirement for these defect characteristics is a shipment without defects. In this context Defect Class 1 means that the packaging material is not utilizable in the form supplied. If the goods can be brought into a utilizable state at little expense by means of reworking this is to be performed. Palette und/oder Außenverpackung entspricht nicht der Vorschrift, beschädigt, verschmutzt (Packmittelspezifikation) /pallet and/or outer packaging does not meet packaging specification, 0.00 0 + @ 1 Packschema falsch / Packaging scheme incorrect 2/3 0,00 ō 0999Kennzeichnung der Palette / 09999 Gebinde muss der Vorschrift entsprechen / 1/3/4/5 0,00 0 + lling of the Pallet / Container must comply with the specification ● ② ● ● Einzelverpackung (Sterilverpackung) beschädigt, verschmutzt, unvollständig / Individual 5/6/7 0.00 0 + ks (Sterile Packing), damaged, soiled, incomplete O SLieferantenstichprobe / Begleitpapiere, Qualitätsdokumente, Prüfzertifikat falsch / fehlen / 8/9 0.00 0 Suppliers random sample / Accompanying documents, quality documents, test certificate incorrect / missing
Untermischung // Intermixing ÷ 00000Untermischung / intermixing 0,00 0 Ausgangsmaterial / Starting material ● ● Das Material (EP Edition 10 - 3.1.3; 3.1.4) (EP Edition 10 - 3.1.5; 3.1.6) / Die Einfärbung 1/2 0,00 0 + muss der Vorschrift entsprechen / The material / The colour must comply with the specification Grundglas, Wasserbeständigkeit der Innenoberfläche/gemäß Glasgrießmethode, Licht-1/2/3/4/5 durchlässigkeit, Farbe entspricht nicht der Vorschrift / Base glass, Water resistant of internal surface 0,00 0 acciglass grain method. Light transmission of base glass, Color of base glass does not meet specification 10 Szusammenhaftende bzw. klebrige Gummiteile / rubber parts adhering to one another or sticking 0,40 0(3)+ Sauberkeit / Cleanlines 🛮 🗗 Verunreinigung-gelangen ins Füllgut / Contamination - gets Into contents, 🛡 😢 🗗 Grenzwerte für 1/5/6/7 Partikel überschritten / Agreed limits for particles exceeded 0,00 0 ●●●Fremdeinschlüsse-Aussehen stark beeinträchtigt, > 1mmø oder Anhäufung • 0mehrere fest anhaftende Fremdkörper, Flecken ≥ 0,2mm2 / lose Partikel/ Foreign bodies enclosed appearance 1/3/8 0,10 0 (1) markedly impaired, > 1mm Ø / Brandstellen flächenförmig / Burn-marks >2mm diameter

odies incorporated in the material / Scorch dots 0,5-2mm Ø

2/4

2/4

10

3/4/7/9/

9 9 Nicht entfernbare Verunreinigungen innen ≥ 0,3mm² / Non-removable contamination inside ≥ 0,3mm²

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm2 / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm2 / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm2 / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm2 / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² außen ≥ 0,5mm² / Removable contamination inside.

• entfernbare Verunreinigungen innen ≥ 0,3mm² / Removable contamination innen ≥ 0,5mm² / Removable contamination innen ≥ 0,5

😚 Brandstellen / Scorched spots 👽 🏵 🗗 Fremdeinschlüsse-Aussehen wenig beeinträchtigt < 1 mm Ø

/ Foreign bodies enclosed- appearance less impaired, < 1mm Ø, Lose Materialreste / Loose material residues

+

+

4

0 (3)

0 (3)

Ω

3 (12)

0,40

0,40

1.00

2.50

ident,-Nr Article no.:	. 6615MA Ihre IdentNr.: CM-2074 Chargen-Nr.: 111585 Your article no.: Batch no.: Verarbeitungsfehler / Processing Errors		Stichprobe: sampling size:	50 (315) quant. (qual)
2/7/15/	Verardellungstenter / Processing Errors	<u> </u>		
17	Shicht ausgeformte Gummiteile, Risse, Riefen, Kerben, Löcher, Dichtigkeit (Funktion) beeinträchtigt / Incompletely formed rubber parts, tears, grooves, notches, hotes, seal and or function impaired / Formgrat, Stanzfehler anhaftetende Fellreste / Flash, punching errors Shisse, Spalten, Löcher, Teile nicht voll ausgespritzt, Fließnaht bricht auf / Tears, clets, hotes, partsincompletely Injected, seam breaks open Durchgehende Risse / Wall penetrating cracks Shanal verstopft keine Doslerung möglich / Duct blocked dossage Impossible, Im Bereich des Abtropfrandes und der dichtenden Flächen geraut-Dichtigkeit nicht gegeben / Roughness in the area of the dropping rim and of the sealing areas-seal not possible	0,00	0	+
1/3/4/9/	Starke Formnähte u./o Rückstände an den Anspritzpunkten / Marked mould Joints and or residues at the			
13	injection points Stark verzogene Teile / Markedly warpeditems �Deformierung / Deformation �� Anspritzpunkt entspricht nicht (seitlich max 0,5mm, zentari max. 0,7mm) / Injection point does not comply (lateral max. 0,5mm, centeral max. 0,7mm) Überspritzungen, �Formgrate an Dichtstellen (Over-injection, flash at the sealing points	0,10	0 (1)	+
8/9/12/	❸ Anrisse / incipient cracks Absplitterungen im Dichtungsbereich / Chipping in area of seal Blasen,			
15/19/ 08.1	Einschlüsse>1,0mm / Gas bubbles, inclusions > 1mm. Kühlspannung außer Toleranz / Cooling stress out of teterance Abgeplatzte Stelle(n), Deformierung/en oder Glasspitze(n) am vorderen Teil (Kugel) / Cipped place(s), deformity(ies) or glass spike(s) on tip (ball) Oberfläche, Kontur uneben / Surface, Shape tuneven	0,40	0 (3)	+
6/8/12/	②verformte Behältnisse / Deformed containers Kratzer (Breite ≥0,2mm, Länge ≥ 20mm) / Scratches			
13	(width ≥ 0,2mmand length ≥ 20mm	2,50	3 (12)	+
建沙猫之	Abmessungen; Gravur; Druck / Dimenskins, Engraved text, Printing	7 JH N		
1	Skanal Ø a.T. / Duct diameter out of telerance, Dosierung/Tropfgeschwindigkeit muss der Vorschrift (Prüfvorschrift nach Vereinbarung) entsprechen / bosage/dropping speed must comply with the specification (testing procedure according or agreement, Verbindungsstege abgerissen- anzahlmäßig mehr als die Hälfte der Stege / Connecting strip tom off-numerically more than half of the studs, ❷ ❸ ⑤ Dichtigkeit / test for	0,00	0	+
1/2/3/6	OScheibel Ø, Tropfloch Ø, Biegung außerhalb der Toleranz / Diameter of annular flange, dropper hole, bend out of the tolerance ⊕ sonstige Maße, Winkel, Radien außer Toleranz / Other dimensions, angles, radii out of tolerance ⊕ Abmessungen a.T. / Dimensions out of tolerance ⊕ weitere Maße außer Toleranz / Other dimensions out of tolerance, Originalitäts-Sicherungsring fehlt / Tamper-proof ring missing	0,10	0 (1)	+
1/3	Gravur fehlt, falsch u./o, unvollständig. / Engraved text missing, incorrect and/or incomplete, Druck, Prägung fehlt, falsch u/o unvollständig / Overprinting,embossed text missing, incorrect and/or incomplete Gewinde fehlt oder ist nur mangelhaft ausgebildet / Thread missing or only inadequately formed Druckfarbe falsch / Printing color incorrect, Druckbild fehlt, falsch / Printing image missing or incorrect	0,00	0	+
1/6/7	Gravur für Dosierung unvollständig - Dosierung nicht möglich / Engraved marks for dosage incomplete - Dosage not possible, Abmessungen entsprechen nicht / Dimensions do not comply, Text fehlt, falsch oder nicht lesbar / text absent, incorrect or illegible, Dosierung a.T. / Dosage out of tolerance,	0,10	0 (1)	+
4	②Druckfarbe haftet nicht / Printing does not adhere	0,40	0 (3)	+
M2018/350	Montage / Mounting	igiyan;	polevicina	Marine Sa
13/15	SKindergesicherter Verschluss-Funktion nicht gewährleistet / Childproof closure-function not ensured, Außenteil gerissen / External part tom	0,00	0	+
1/2/4/5/ 9/17/19	● ● Seinzeltell fehlt / Individual parts missing, Teile durch Montage beschädigt / Parts demaged by mounting. Teile falsch montiert / Parts incorrect mounted, ● Pipette zu tief in Sauger eingesetzt / Pipette set too deep into the teat, Tropfeinsdatz durch Montage beschädigt / Dropper insert demaged by mounting	0,10	0 (1)	+

falls zutreffend die dazugehörige Fehlerbewertungsfiste if applicable the relevant Defect Evaluation List

(1) Skip-Lot verfahren; skip-batch Process

OKunststoff-Stopfen, Trockenkapseln und Aufsteckkappen / Plastic Stoppers, Desiccators and Caps OBehältnisse aus Röhrenglas / Containers Made of Tubular Glass 🔞 Gummiteile / Rubber Parts 🐠 Spritzgussteile aus Kunststoff: Verschlüsse; Dichteinlagen und Dosierhilfen (Tropfer etc.) / Injection-moulded Parts Made of Plastic: Closures SApplikatoren und Messeinrichtungen aus Kunststoff / Applicators and Measuring Devices Made of Plastic

Hiermit bestätigen wir, dass die Qualität des oben bezeichneten Produktes nach den gültigen Prüfnormen (*Sterilität entsprechend ISO 11135 bzw. 11137 in der jeweiligen aktuellen Ausgabe) gemäß Spezifikation (Ausführungsvorschrift, technischer Zeichnung) sowie der jeweils gültigen Fehlerbewertungsliste hergestellt, verpackt, *sterilisiert und geprüft wurden und die dabel zulässigen Grenzwerte nicht überschritten wurden. Soweit für das obige Produkt abweichende Vereinbarungen zwischen Hersteller bzw. Lieferant und Verwender (Kunden) bestehen, werden diese zugrunde gelegt. We hareby confirm that the quality of the products described above has been produced, packed, "sterilized, inspected and tostel in accordance with the valid inspection and testing standards ("Sterility conforming ISO 11135 or 11137 in its current version] according to the specification (documentet procedure, technical drawing) and the Defect Evaluation List and did not exceed the permissible limits. Where alternative aggreement for the above product exist between the costumer and the manufacturer and/or supplier, the relevant values have been based on

*falls zutreffend / if applicable

Vereinbarte Artikelspezifikationen beinhalten die Unbedenklichkeit der Materialien nach Verordnung (EU) Nr. 10/2011, 1935/2004, RL94/62/EG 1907/2006, 1223/2009,deren Herstellung nach2023/2006 und deren aktuellen Ergänzungen. Gleichzeitig wird die Konformität nach ISO 13485(aktuelle Ausgabe) und RL 93/42/EWG (Verordnung 2017/745) bestätigt Agreed article Specifications includes the compliance of the materials with EU-regulations 10/2011/EC, 1935/2004/EC, guideline 94/62/EC, 1907/2006/EC, 1223/2009/EC, whose manufacturing based on 2023/2006/EC and the current amendments. At the same time, conformity with ISO 13485 (current edition) and RL 93/42 / EEC (Regulation 2017/745) is confirmed.

Für Folgeschäden beim Kunden (unerwartete Unterbrechung an Abfüllanlage, Prüfaufwand, Rückruf usw.), wird keine Haftung übernommen solange die Vorgaben gemäß Fehlerbewertungsliste eingehalten sind. For secondary fallures by the costumer (secondary failures bottling plant, additional fests, product recall etc.), to assume no liability as lang as the standard in accord with Defect Evaluation List are adhered to.

Vorstehende Angaben entbinden nicht von der Durchführung einer Wareneingangskontrolle The above particulars do not release the customer from the of obligation to carry out an inspe

Date:

Datum: 31.08.2022

Freigabe:

Prüfer: i.A.



Simplified joint stock company with capital of 44 081 866 Euros -Nanterre Trade and Companies Register N°B552 012 585 - VAT I/D: FR 29 552 012 585

Head Office and Sales Departements: Tour CB16 - 17 place des Reflets - 92097 Paris La Défense Cédex - France. Phone:+33(0)1 40 90 36 00 - Fax:+33(0)1 40 90 36 01 Postal address: Tour CB 16 - 17 place des Reflets - CS 30300

92097 Paris La Défense Cédex - France

The

21.07.2022

Customer

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371

71201

Delivery adress

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371001

LOD

LOD

IL

IL

Customer's order

PO22000396

from 12.05.2022

Customer's product code

CM-2052

Delivery

81491445

Quantity Delivered

17.160 PCE

SGD Product Code

52490 04 001

TROPFFLASCHE 10 ML None

type 3 AMBER GLASS

SGD Drawing N 68713G Run Number

Treatment N 221273

Manufacturing Date

02.05.2022 to

09.05.2022

Quantity per Pallet

17.160

Production Site

SUCY EN BRIE

France

Glass quality

	Unit	Specif	ications	Res	Results		
		Min	Max	Min	Мах	Ave	S∹D
Arsenic	ppm		0,100	0,050	0,050	0,050	0,000
Hydro-resist-powder/lg	m1		0,830	9,390	0,590	0,590	6,000
Hydrolytic resistance (HCl)	m)		8,100	6,400	7,000	6,730	0,310
Spectral transmission	ŝ		10,000	0,920	0,929	0,920	3,600
Annealing			18,000		Conf	orms	£

Glass measurements

	Unit	Specifi	cations	Results			
		Min	Маж	Min	Max	Ave	S-D
Minor thread diameter	mis	15,680	15,580	15,730	15,850	15,794	0,035
Opening diameter	man	10,450	10,750	10,520	10,720	10,611	0,046
Body diameter	IEE	25,000	25,800	25,180	23,540	25,375	0,041
Mini Internal bore	nai	9,500		10,960	11,800	11,385	0,179
Neck finish height 2	‡ntes	10,800	11,200	10,040	11,170	10,991	0,070
Maxi External neck	HALS		18,000	17,730	17,935	17,815	0,045
Total height	ttan	57,400	58,600	9 7, 650	58,230	58,015	0,119
Neck finish diameter	na	17,705	18,000	17,700	17,800	17,741	0,027
Bead diameter	nun.	19, 300	20,200	19,840	20,050	19,993	0,041
Neck finish height	ma	13,500	13,900	13,510	13,740	13,644	a,052



SGI) S.A. Simplified joint stock company with capital of 44 081 866 Euros -Nanterro Trade and Companies Register N°B552 012 585 - VAT I/D: FR 29 552 012 585

Head Office and Sales Departements: Tour CB16 - 17 place des Reflets - 92097 Paris La Défense Cédex - France. Phone:+33(0)1 40

90 :36 :00 - Fax:+33(0)1 :40 :90 :36 :01 Postal address : Tour CB :16 - 17 place des Reflets - CS :30300 -92097 Paris La Défense Cédex - France

CERTIFICATE OF QUALITY

The

21.07.2022

Customer

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371

71201

LOD

IL

Delivery adress

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371001

LOD

IL

Customer's order

PO22000396

from 12.05.2022

Customer's product code

CM-2052

17.160 PCE

Delivery

81491445

Quantity Delivered
TROPFFLASCHE 10 ML

,,,,,,,

SGD Product Code SGD Drawing N 68713G 52490 04 001 Treatment

None

type 3 AMBER GLASS

09.05.2022

Run Number

N 221273

Manufacturing Date
Production Site

02.05.2022 to

J9.05.2024

Quantity per Pallet

17.160

SUCY EN BRIE

France

Glass characteristics

	Unit	Specifications		Results			
		Min	Max	Min	Max	Ave	S-D
Weight				33,600	25,000	24,321	0,315
Capacity	m2	13,000	15,000	13,805	14.800	14,209	0,304
Vertical load	kg/cm	200,000		400,000	400,000	400,000	0,000
Thermal shock		42,090			Conf	orms	

Quality Manager

Laurent MILLET

MU

Approved
Signature: _____

Date:_

22.08.22

2.R. 22 Cd. 22



Customer ...: FANAXIA FHARMACEUTICAL IND.

F.a.o.: QUALITY DEPARTMENT

Temse.

4/06/2021

CERTIFICATE OF CONFORMITY

This delivery contains the following articles:

Quantity	Description + Item customer	Your ref.
50000	CAP	P021000337 dd. 09/03/2021
	560 PP 099 WHITE CM-2054	Our ref./Batch no
		21-0443/00
		50000 CAP 560 PP 099 WHITE

Approved by :

Patricia Raes Dispatch department

We certify that the above components have been subject to in-process control and, if applicable, other testing. They comply with the agreed specification and were manufactured using the agreed materials, according a certified quality management system to ISO 9001:2015. EN ISO 13485:2016 and EN ISO 15378:2017.

Released by :

Nathalie Van Assche QA department

Approved By QA Signature dud comede Date: 30043022

This document is created electronically and is valid without signature.

Pharmaceutical Industries		ceutical Malta (Opera ar, B'Buga BBG 3000,		
Document title	PRT Number	Document type	Document No.	Version
COA for 10 mL bottles, Type 3 amber glass	PK-000034-MT	COA	F-SPC-113-49-MT	03
Effective date: 10/10/2021			Page 1 of 3	

Article number	Manufacturer	Item
5249004001	SGD Pharma	10mL, type 3 amber glass bottles

Manuf. Batch No:	Panaxia Batch No:	Manuf. Expiry Date:
N 231232	23 33 4-117	09/05/2023

1.0 Specifications:

Test	Test Method*	Specificat	ions	Results (average)
Specifications and Des	cription:		· ·	
		Arsenic	<0.100 ppm	0.003
		Hydro-resist-powder/1g	<0.850 mL	0.570 -
Glass Quality	Supplier COA	Hydrolytic resistance (HCL)	<8.100 mL	7.710 -
	• • • • • • • • • • • • • • • • • • • •	Spectral transmission	<10.000%	1.630
		Annealing	<18.000	Complies
		Minor thread diameter	15.680 - 15.980 mm	15.765
		Mini internal bore	>9.500 mm	11.484
	Supplier COA	Neck finish height 2	10.800 – 11.200 mm	10.984
Glass Measurements		Maxi external neck	<18.000 mm	17.856
Class Measurements		Opening diameter	10.450 – 10.750 mm	10:696 -
		Neck finish diameter	17.700 – 18.000 mm	17.740 -
7		Bead diameter	19.800 – 20.200 mm	19.985 -
		Neck finish height	13.500 – 13.900 mm	13.610 -
		Capacity	13.000 – 15.000mL	13.826
Glass characteristics	Supplier COA	Vertical load	>200.000 Kg/cm	400,000
		Thermal shock	>42.200	Comples
Color	Supplier COA	Amber		Complies Complies
Length (L)	Measure Length using Calibrated Ruler	58.60 – 57.40 mm		57.96
Body Diameter (D)	Measure Length using Calibrated Caliper	25.80 – 25.00 mm		25.435 *-
Appearance (bottom)	Check if designated mark is present on bottom side	10 mL mark		25.435 *-


Equipment/Instrument used:	Equipment/Instrument ID:
Calibrated Caliper	CAL- OI- MT
Calibrated Ruler	RUL-DI-MT
	*DV 20/11/2023

	AUTHORIZATION	
ISSUED BY:	QC APPROVED BY:	QA APPROVED BY:
INITIALS AND DATE:	INITIALS AND DATE:	INTERIS AND PATER LORISED
\$ 3d on 204	3 J - CG-	2021 2GID FUX

ESOS VOU JS

INITIALS: 2 C NOVE 2023

Pharmaceutical Industries				
Document title	PRT Number	Document type	Document No.	Version
COA for 10 mL bottles, Type 3 amber glass	PK-000034-MT	COA	F-SPC-113-49-MT	03
Effective date: 10/10/2021			Page 2 of 3	



2.0 Packaging and Labeling

- Each package must be labeled, by the manufacturer, with at least the following information:
 - 2.1.1 Supplier name and address
 - 2.1.2 Quantity per bag
 - 2.1.3 Supplier article number and description
 - 2.1.4 Supplier batch number
 - 2.1.5 Packed on
- Expiry date: 6 years from manufacturing date (Specified on SGD supplemented documentation)

3.0 Storage conditions:

e conditions:

Store in a cool dry location at a temperature lower than 30°C.

Sample Number	Length (mm)	Body Diameter (mm)		
1	57.5	25.38		
2	58.0	25.43		
3	57.5	25.49		
4	58.0	25.40		
5	57.5	25.47		
6	58.0	25.26		
7	58.5	25.52		
8	58 0	25.40		
9	58.0	25.47		
10	58.0	25:59		

•		PASS □ FAI	L		
Analysed by: Denise Vella Signature: DV			Date: 20/11/2023		
Following the meeting/not n	neeting Panaxia's Sp	pecifications and requirement, h	sting, the batch concerned is considered ence this batch is: Approved/ Rejected.		
11	5	1.5	25.52		
12 580		.0	25.47		
13	58.	5	25.43		
1/1	FO. 8		25.46		

	AUTHORIZ	ATION			INTO
ISSUED BY:	QC APPROVED BY:		QA APPROVED	BY: ALITHOIS	HOLD
INITIALS AND DATE:	INITIALS AND DATE:		INITIALSAND	DATE:	
3d 59/204		3 0 -09- 2021)A(:	-1C- 20COPT	
					DATE: N
			11	VITIALS	LON 20
YUM 10				-	50 110

201 VON 15



Customer ...: PANAXIA PHARMACEUTICAL MALTA (OPERATIONS) LT

F.a.o.: QUALITY DEPARTMENT

Temse,

2/04/2024

CERTIFICATE OF CONFORMITY

This delivery contains the following articles :

. 20/03/2024
h no
-

Approved by :

Jimmy De Bergé Dispatch department

We certify that the above components have been subject to in-process control and, if applicable, other testing. They comply with the agreed specification and were manufactured using the agreed materials, according a certified quality management system to ISO 9001:2015, EN ISO 13485:2016 and EN ISO 15378:2017.

Released by :

Gianina Sarman QA department



COMPANY / UNTERNEHMEN: DATE / DATUM: 14/12/23

Remy & Geiser GmbH

Ein Unternehmen der Bormioli Pharma Group Sitz: Remy & Geiser Straße 1 98553 Schleusingen (OT Hinternah), Germany

DECLARATION OF CONFORMITY	KONFORMITÄTSERKLÄRUNG

ARTICLE / ArtCode	8840MA-AR240001
DELIVERY NOTE / Lieferschein Nr	23004312
CUSTOMER ARTICLE ID / Kunde ArtCode	
DESCRIPTION / ArtBez.	KINDERGESICHERTER VERSCHLUSS KG KPV OVII 6,0 /SPRITZEN- EINSATZ TYP II NW18 W/W/TR
BATCH / Chargen-Nr	H23015_22204693
PRODUCTION DATE / Herstelldatum	06/12/23
SHELF LIFE / Verfalldatum	09/01/2028
PLANT ADDRESS / Adresse der Produktionsstätte	WERK IV REMY & GEISER STRASSE 1 98553 SCHLEUSINGEN DE GERMANY
CUSTOMER / Kunde	Panaxia Pharmaceutical Industries
ORDER NUMBER / AuftrNr.	20077278
CUSTOMER ORDER NUMBER / Kunde AuftrNr.	PO23000265
QUANTITY DELIVERED (kpcs) / Stückzahl (kpcs)	64 KP

We declare that the goods referred to the lot indicated above, received with the supply indicated in the aforementioned delivery note and attached to this document, have been tested and resulted to be IN ACCORDANCE with the product technical specifications and Defect Evaluation List by Editio Cantor Verlag Aulendorf, in the respective valid version – please refer to tables related to the supplied items category in the following pages.

Sampling plan: ISO 2859-1; level II; normal inspection

The control method and quality level of the supply, unless different specifications agreed with the Customer, are those defined in our Quality System.

The above particulars do not release the customer from the obligation to carry out an inspection of the received goods.

Kindly not that we cannot guarantee the suitability of the used material.

In order to ensure that your packaging system works safely, we recommend you perform tests with the corresponding liquid.

According to its formulation, the materials used to manufacture the supplied item comply with the following provisions:

Regulations applicable to articles intended for contact with food:

- Reg. 10/2011 EU and following amendments
- Reg. 1895/2005/EC; Reg. 1935/2004/EC; Reg. 2023/2006/EC
- REACH regulation 1907/2006/EC
- Reg. 1223/2009/EC and following amendments
- Reg.2023/2006/EC and following amendments
- Dir 94/62/EC: relative to the content of heavy metals
- Class I Medical Devices DoC: refer to product specification.

COMPONENT	COMPONENT DESCRIPTION			
LI 1731M-AR240001	KINDERGESICHERTES EINZELTEIL KG ÜK NW18 W			
L1 4509M-AR240001	KINDERGESICHERTES EINZELTEIL KG KSK OVII TYP V; VI; VII 6,0 N			
L1 8805A-AR240001	DOSIERHILFE SPRITZEN-EINSATZ TYP II NW18 TR			

VIATERIAL 30147 COMPONENT

MATERIAL DESCRIPTION

1731M-AR240001

PURELL ACP 6541 A



Pag. 2

B0658 1731M-AR240001 FARBKONZENTRAT WEISS REMAFIN-EP-WEISS PL00075542-ZT ähnlich

B0658 4509M-AR240001 B0147

RAL 9016 2%ig FARBKONZENTRAT WEISS REMAFIN-EP-WEISS PL00075542-ZT ähnlich

RAL 9016 2%ig

PURELL ACP 6541 A

B0143 8805A-AR240001

4509M-AR240001

PURELL PE1840H NATUR

Plant Quality Manager/ Qualitätsmanager für den Produktionsstandort

Benny Mueller



PRÜFZERTIFIKAT NACH FEHLERBEWERTUNGSLISTE (EDITIO CANTOR VERLAG) 18, 19, 20, 22, 34 aktuelle Ausgabe Test Certificate acc. to Defect Evaluation List (Editio Cantor Verlag) Vol. 18, 19, 20, 22, 34 in current edition

Angaben zur Lagerung: Es bestehen keine besonderen Anforderungen an Temperatur und Luftfeuchtigkeit. Jedoch sind häufige, große Temperaturschwankungen zu vermeiden damit sich kein Kondenswasser bildet. Ferner sollte die Einwirkung von Temperaturen über 45°C vermieden werden um Verformungen auszuschließen.

Storage conditions: There are no special requirements to temperature or humidity. However, high fluctuations in temperature have to be avoided, so that no condensation could be caused. Furthermore, a temperature above 45°C should be avoided, to prevent deformation.

Fehler-Nr. Attrno.	Fehler/Einzelmerkmal Defect/Individual characteristics	AQL	Entscheidung Result
3 3 7 3 7 2 8 2 3	Anlieferung, Kennzeichnung, Verpackung / Delivery, labelling, packing	410 eyeşile 20adı	
Prüfung diese Lieferung. Fel Lässt sich die The defect char applicable for the Defect Class 1 in	wrkmale beziehen sich hier nicht auf das Packmittel selbst, sondern auf Paletten und Palet Fehlermerkmale ist kein Stichprobenverfahren anwendbar. Die Vergabe bezüglich diesel nierklasse 1 bedeutet in diesem Zusammenhang, dass das Packmittel in der vorliegenden Alware mit geringem Aufwand durch Nachbesserung in einen verwendbaren Zustand bringen, racteristics refer not to the packaging material itself but to the pallets and packaging units (containers testing of these defect characteristics. The requirement for these defect characteristics is a shipme means that the packaging material is not utilizable in the form supplied. If the goods can be brought into a king this is to be performed.	r Merkmale nlieferform n so ist dies d). No random ent without de	ist eine fehlerfreie licht einsetzbar ist. urchzuführen. sampling method is fects. In this context
18.01,01 19.01.01 20.01.01 22,01.01	(1)(3)(4)(5)(6) Palette und/oder Außenverpackung entspricht nicht der Vorschrift, beschädigt, verschmutzt (Packmittelspezifikation) /pallet and/or outer packaging does not meet packaging specification, damaged,soiled	**	+
19.01.04 20.01.02 /03	(1)(3)(4)(5)(6) Packschema falsch / Packaging scheme incorrect	**	+
18.01.03/04 19.01.06 20.01.06 22.01.03/04	(1)(3)(4)(5)(6) Kennzeichnung der Palette / (1)(3)(4)(5)(6) Gebinde muss der Vorschrift entsprechen / Labelling of the Pallet / Container must comply with the specification	-	+
18.01.05/07 19.01.09/10 20.01.08 22.01.05/06	(1)(3)(4)(5)(6) Einzelverpackung (Sterilverpackung) beschädigt, verschmutzt, unvollständig / Individual packs (Sterile Packing), damaged, soiled, incomplete	-	+
20,01,09/10	(1)(3)(4)(5)(6) Lieferantenstichprobe / Begleitpapiere, Qualitätsdokumente, Prüfzertifikat falsch / fehlen / Suppliers random sample / Accompanying documents, quality documents, test certificate incorrect / missing	-	+
	Untermischung / Intermixing		
18.03.01 19.02.01/02 20.02.01 22.03.01	(1)(3)(4)(5)(6) Untermischung / Intermixing		+
	Ausgangsmaterial / Starting material		
1,1,1/2 18,02,01/02 19,03,05 22,02,01/02	(1)(3)(4)(5)(6) Das Material (EP Edition 10 - 3.1.3; 3.1.4) (EP Edition 10 - 3.1.5; 3.1.6) / Die Einfärbung muss der Vorschrift entsprechen / The material / The colour must comply with the specification	•	+
20.04.10	(3)(6) Zusammenhaftende bzw. klebrige Gummiteile / rubber parts adhering to one another or sticking	0,40	+
an cena és e	Sauberkeit / Cleantines	在4000000000000000000000000000000000000	
4.4.1 18.04.01/05/06 20.07.02 22.04.01/05/06	(1)(3)(4)(5)(6) Verunreinigung-gelangen ins Füllgut / Contamination - gets into contents, (1)(3)(4) Grenzwerte für Partikel überschritten / Agreed Ilmits for particles exceeded	-	+
)4.04.08 22.04.01 '03	(1)(4)(5)(6) Fremdeinschlüsse-Aussehen stark beeinträchtigt, > 1mmØ oder Anhäufung (3) mehrere fest anhaftende Fremdkörper, Flecken ≥ 0,2mm2 / lose Partikel/ Foreign bodies enclosed appearance markedly impaired, > 1mm Ø / Brandstellen flächenförmig / Burn-marks > 2mm diameter	0,10	+
18.04.02 22.04. 04	(1)(4)(6) Im Material eingeschlossene Fremdkörper / Brandstellen punktförmig 0,5- 2mm Ø / Foreign bodies incorporated in the material / Scorch dots 0,5- 2mm Ø	0,40	+
)4.04.09 }2.01.04	(5) Brandstellen / Scorched spots (1)(4)(5)(6) Fremdeinschlüsse-Aussehen wenig beeinträchtigt < 1mm Ø / Foreign bodies enclosed- appearance less Impaired, < 1mm Ø, Lose Materialreste / Loose material residues	2,50	+
	Verarbeitungsfehler / Processing Errors		
3.5.5 12.05.07	(3) Nicht ausgeformte Gummiteile,Risse, Riefen, Kerben, Löcher, Dichtigkeit (Funktion) beeinträchtigt / Incompletely formed rubber parts,tears, grooves, notches, holes, seal and or function impaired / Formgrat, Stanzfehler anhaftetende Fellreste / Flash, punching errors (4)(5) Risse, Spalten, Löcher, Teile nicht voll ausgespritzt, Fließnaht bricht auf / Tears, clets, holes, partsincompletely injected, seam breaks open (4) Kanal verstopft keine Dosierung möglich / Duct blocked dossage impossible, Im Bereich des Abtropfrandes und der dichtenden Flächen geraut-Dichtigkeit nicht gegeben / Roughness in the area of the dropping rim and of the sealing areas-seal not possible	-	+

Pag. 4

₹		ray.	4
Fehler-Nr. Attrno.	Fehler/Einzelmerkmal Defect/Individual characteristics	AQL	Entscheidung Result
	Verarbeitungsfehler / Processing Errors		
5.5.1 22.05,06/03/09	(5) Starke Formnähte u./o Rückstände an den Anspritzpunkten / Marked mould joints and or residues at the injection points Stark verzogene Teile / Markedly warpeditems (4) Deformierung / Deformation (1)(4) Anspritzpunkt entspricht nicht (seitlich max 0,5mm, zentarl max. 0,7 mm) / Injection point does not comply (lateral max. 0,5mm, centeral max. 0,7mm) Überspritzungen, (4) Formgrate an Dichtstellen (Over-injection, flash at the sealing points	0,10	+
18.05.12 22.05.08/09	(1) Oberfläche, Kontur uneben / Surface, Shape uneven	0,40	+
19.03.13 22.05.12	(4)(5)(6) Falten, Kerben, Kratzer, Formgrat / Folds, notches, scratches, flash	2,50	+
	Abmessungen; Gravur; Druck / Dimensions; Engraved text; Printing		
9.9.1 22.06.01	(4) Kanal Ø a.T. / Duct diameter out of telerance, Dosierung/Tropfgeschwindigkeit muss der Vorschrift (Prüfvorschrift nach Vereinbarung) entsprechen / Dosage/dropping speed must comply with the specification (testing procedure according or agreement, Verbindungsstege abgerissenanzahlmäßig mehr als die Hälfte der Stege / Connecting strip tom off-numerically more than half of the studs, (3)(4) Dichtigkeit / test for leaks, Originalitäts-Sicherungsring fehlt / Tamper-proof ring missing	_	+
18.06.03.01 20.09.01 22.06.01.01	(1) Sonstige Maße, Winkel, Radien außer Toleranz / Other dimensions, angles, radii out of tolerance (3) Abmessungen a.T. / Dimensions out of tolerance (4) weitere Maße außer Toleranz / Other dimensions out of tolerance	0,10	+
18.07.01 19.18.05 22.07.01	(1)(4)(6) Gravur fehlt, falsch u./o. unvollständig. / Engraved text missing, incorrect and/or incomplete, Druck, Prägung fehlt, falsch u/o unvollständig / Overprinting, embossed text missing, incorrect and/or incomplete Gewinde fehlt oder ist nur mangelhaft ausgebildet / Thread missing or only inadequately formed (4)(6) Druckfarbe falsch / Printing color incorrect, Druckbild fehlt, falsch / Prinzting image missing or incorrect	-	+
07.07.01 18.07.07 19.18.06 22.07.01/03	(5)(6) Gravur für Dosierung unvollständig - Dosierung nicht möglich / Engraved marks for dosage incomplete - Dosage not possible, Abmessungen entsprechen nicht / Dimensions do not comply, Text fehlt, falsch oder nicht lesbar / text absent, incorrect or illegible, Dosierung a.T. / Dosage out of tolerance, (1)(4)(6) Farbe, Prägefolie-Haftung nicht ausreichend / Colour, embossed film-not resistant to abrasion	-	+
845 144 15 15 15 15 15 15 15 15 15 15 15 15 15	Montage / Mounting		
22.08.13/15	(4)(6) Kindergesicherter Verschluss-Funktion nicht gewährleistet / Childproof closure-function not ensured, Außenteil gerissen / External part torn	-	1.
18.08.01/03/04 22.08.05/17/18	(1)(4)(5)(6) Einzelteil fehlt / Individual parts missing, Teile durch Montage beschädigt / Parts demaged by mounting, Teile falsch montiert / Parts incorrect mounted, (4)(6) Pipette zu tief in Sauger eingesetzt / Pipette set too deep into the teat, Tropfeinsdatz durch Montage beschädigt / Dropper insert damaged by mounting	0,10	+
	Fertigungsfehler Pipetten / Manufacturing defects Pipettes		
19.08.01	(6) Abgeplatzte Stelle/n, Deformierung/en, oder Glassspitze/n am vorderen Teil (Kugel) / Chipped arera(s), defomation or glass spike/s on the tip	0,25	+

* falls zutreffend die dazugehörige Fehlerbewertungsliste * if applicable the relevant Defect Evaluation List

+:Passed - Non passed

(1) Kunststoff-Stopfen, Trockenkapseln und Aufsteckkappen / Plastic Stoppers, Desiccators and Caps • (3) Gummiteile / Rubber Parts

(4) Spritzgussteile aus Kunststoff: Verschlüsse; Dichteinlagen und Dosierhilfen (Tropfer etc.) / Injection-moulded Parts Made of Plastic: Closures

(5) Applikatoren und Messeinrichtungen aus Kunststoff / Applicators and Measuring Devices Made of Plastic (6) Pipetten Monturen/Glass Pipette Dropper

Hiermit bestätigen wir, dass die Qualität des oben bezeichneten Produktes nach den gültigen Prüfnormen (*Sterilität entsprechend ISO 11135 bzw. 11137 in der jeweiligen aktuellen Ausgabe) gemäß Spezifikation (Ausführungsvorschrift, technischer Zeichnung) sowie der jeweils gültigen Fehlerbewertungsliste hergestellt, verpackt, *sterilisiert und geprüft wurden und die dabei zulässigen Grenzwerte nicht überschritten wurden. Soweit für das obige Produkt abweichende Vereinbarungen zwischen Hersteller bzw. Lieferant und Verwender (Kunden) bestehen, werden diese zugrunde gelegt. We hereby confirm that the quality of the products described above has been produced, packed, *sterilized, nspected and testet in accordance with the valid inspection and testing standards (*Sterility conforming ISO 11135 or 11137 in its current version)according to the specification (documentet procedure, technical drawing) and the Defect Evaluation List an did not exceed the permissible limits. Where alternative aggreement for the above product exist between the costumer and the manufacturer and/or supplier, the relevant values have been based on these.

*falls zutreffend /*if applicable

Für Folgeschäden beim Kunden (unerwartete Unterbrechung an Abfüllanlage, Prüfaufwand, Rückruf usw.), wird keine Haftung übernommen solange die Vorgaben gemäß Fehlerbewertungsliste eingehalten sind. For secondary failures by the costumer (secondary failures pottling plant, additional tests, product recall etc.), to assume no liability as lang as the standard in accord with Defect Evaluation List are adhered to.

Vorstehende Angaben entbinden nicht von der Durchführung einer Wareneingangskontrolle The above particulars do not release the customer from the of obligation to carry out an inspection of goods received



SGD S A

Simplified joint stock company with capital of 44 081 866 Euros -Nanterre Trade and Companies Register N°B552 012 585 - VAT I/D : FR 29 552 012 585

Head Office and Sales Departements: Tour CB16 - 17 place des

Reflets - 92097 Paris La Défense Cédex - France. Phone:+33(0)1 40 90 36 00 - Fax:+33(0)1 40 90 36 01 Postal address: Tour CB 16 - 17 place des Reflets - CS 30300 -

92097 Paris La Défense Cédex - France

CERTIFICATE OF QUALITY

The

23.05.2023

Customer

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371

71201

LOD

ΙL

Delivery adress

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371001

LOD

IL

Customer's order

PO23000121

from 25.04.2023

Customer's product code

CM-2048

9.702

Delivery

81521342

Quantity Delivered TROPFFL. 30 ML

PCE

SGD Product Code SGD Drawing N 69676I 02543 07 020 Treatment

None

Production Site

type 3 AMBER GLASS

Run Number

N 231206

Manufacturing Date

03.04.2023 to

11.04.2023

Quantity per Pallet

9.702

SUCY EN BRIE

France

We, SGD S.A., hereby certify that the above referred bottles have been tested and are in conformity with:

THE SPECIFICATIONS IN FORCE

TO THE CURRENT ISO 15378 VERSION

THE HYDROLYTIC RESISTANCE

- To the requirements of the European Pharmacopoeia in force
- To the requirements of the USP in force
- Hydrolytic Resistance testing Grain is done at least once per year.

ARSENIC

- To the requirements of the European Pharmacopoeia in force
- To the requirements of the USP in force
- Arsenic tests are carried out once per year by Furnace

SPECTRAL TRANSMISSION

- To the requirements of the European Pharmacopoeia in force
- To the requirements of the USP in force





Simplified joint stock company with capital of 44 081 866 Euros Nanterre Trade and Companies Register N°B552 012 585 - VAT I/D: FR 29 552 012 585

Head Office and Sales Departements : Tour CB16 - 17 place des Reflets - 92097 Paris La Défense Cédex - France. Phone:+33(0)1 40 90 36 00 - Fax:+33(0)1 40 90 36 01

Postal address: Tour CB 16 - 17 place des Reflets - CS 30300 -

92097 Paris La Défense Cédex - France

CERTIFICATE OF QUALITY

The

23.05.2023

Customer

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371

71201

LOD

ΙL

Delivery adress

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371001

LOD

ΙL

Customer's order

PO23000121

from 25.04.2023

Customer's product code

CM-2048

Delivery

81521342

Quantity Delivered TROPFFL. 30 ML

9.702 PCE

SGD Product Code SGD Drawing N 69676I 02543 07 020 Treatment

None

type 3 AMBER GLASS

Run Number

N 231206

Manufacturing Date

03.04.2023 to

11.04.2023

Quantity per Pallet

9.702

Production Site

SUCY EN BRIE

France

Glass quality

	Unit	Specifications Resul		lts			
		Min	Max	Min	Max	Ave	S-D
ARSENIC	ppm		0,100	0,050	0,050	0,050	0,000
Hydro-resist-powder/1g	ml		0,850	0,590	0,590	0,590	0,000
Hydrolytic resistance (HCl)	ml		6,100	4,640	4,940	4,790	0,150
Spectral transmission			10,000	1,630	1,630	1,630	0,000
Spectral transmission Annealing			18,000	Conforms			

Glass measurements

	Unit	Specifications		Results			
	-	Min	Max 32,900	Min 32,120	Max	Ave 32,206	S-D 0,034
	mm	31,900			32,270		
Body diameter		9,500		10,930	11,820	11,483	0,186
Mini Internal bore	mm	15,680	15,980	15,760	15,870	15,815	0,026
Minor thread diameter		10,800	11,200	10,970	11,090	10,999	0,032
Neck finish height 2	mm	10,800	18,000	17,710	17,960	17,830	0,055
Maxi External neck	mm				10,740	10,660	0,049
Opening diameter	mm	10,450	10,750	10,570	10,740	20,000	
Body diameter	mm	31,900	32,900		<u> </u>	ļ	0.100
Total height	mm	78,500	80,100	79,250	79,850	79,475	0,108
	ium	17,700	18,000	17,710	17,810	17,745	0,026
Neck finish diameter		19,800	20,200	19,900	20,070	20,002	0,039
Bead diameter	Ling			13,530	13,700	13,610	0,040
Neck finish height	TOUT	13,500	13,900	1 23,330			1





Simplified joint stock company with capital of 44 081 866 Euros -Nanterre Trade and Companies Register N°B552 012 585 - VAT I/D :

FR 29 552 012 585

Head Office and Sales Departements: Tour CB16 - 17 place des Reflets - 92097 Paris La Défense Cédex - France. Phone:+33(0)1 40 90 36 00 - Fax:+33(0)1 40 90 36 01

Postal address: Tour CB 16 - 17 place des Reflets - CS 30300 -92097 Paris La Défense Cédex - France

CERTIFICATE OF QUALITY

The

23.05.2023

Customer

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371

71201

LOD

1L

Delivery adress

PANAXIA PHARMACEUTICAL INDUSTRIES / 39371001

LOD

IL

Customer's order

PO23000121

from 25.04.2023

Customer's product code

CM-2048

Quantity Delivered

PCE

Delivery

81521342

TROPFFL. 30 ML

9.702

SGD Product Code SGD Drawing N 69676I 02543 07 020

None

type 3 AMBER GLASS

Run Number

Treatment N 231206

Manufacturing Date

03.04.2023 to

11.04.2023

Quantity per Pallet

9.702

Production Site

SUCY EN BRIE

France

Glass characteristics

	Unit	Specifications		Results			
		Min	Max	Min	Max	Ave	s-p
Weight	g			40,600	42,000	41,208	0,331
Capacity	ml	34,300	36,700	34,900	35,900	35,420	0,223
Vertical load	kg/cm	200,000		400,000	400,000	400,000	0,000
Thermal shock		42,000		Conforms			

Quality Manager

Laurent MILLET

Certificate of Conformity



Panaxia Pharmaceutical Malta (Operations) LTD

HHF001A Ħal Far Birżebbuġa MALTA

MT26344313



Call: +44 (0) 1482 638380

Melton House Wyke Way Melton East Yorkshire HU14 3HJ

Email: info@originItd.com

www.originltd.com

Account Ref: Certificate No Customer Order No PANA003 115312 v1 PO23000457

Date

22/05/2024

Product Code		Product Description		No of Cases	Unit Qty	Qty Despatched
OS1W3-W	1ml White Oral Dosage Syringe - 0.01ml Graduations - Wrapped			20,000.00	1.00	20,000
Your Prod Code:	PK00 Batch 1	00221-MT				
	#	Batch P0057883	Quantity 20,000	Manufacturer Batch Ref BRV240313		
OS1W3-W Your Prod Code:		1ml White Oral Do 0.01ml Graduations 00221-MT		30,000.00	1.00	30,000
	# 1	Batch P0057883	Quantity 30,000	Manufacturer Batch Ref BRV240313		

Deliver To:

Panaxia Pharmaceutical Malt HHF001A Hal Far Birżebbuġa MALTA

Certificate of Conformity

We confirm that the products detailed herein have been supplied from a QA approved source and have been manufactured, inspected and tested in accordance with the manufacturers





CERTIFICATE OF ANALYSIS

Product: 1ml Dosing Syringe Product Code: SYPN01-WH - CE Batch/Lot No.: BRV240313 A.R. No.: FG-24-0698 MFG Date: 08/05/2024

Date: 13/05/2024 Batch/Lot size: 30,000 NOS Challan No.: EXP/4/2024-25 Exp Date: 3 Years from MFG.

Party's Name: Origin Packaging Ltd.

St. No	Tests	Specification	Physicalle
		1ml Dosing syringe marked at volume of 0.05ml, 0.06ml,	Results
A	Description 0.07ml, 0.08ml, 0.09ml up to 1ml with instruction (FOR ORAL USE ONLY) with individual BOPP sealing and CE0123		Complies
		mark.	
		Should confirm with	
		(I) Colour	
		Barrel: Natural (Markings in Black Ink),	
В	Appearance	Plunger: WHITE (PL00075542) *	- N
	• • • • • • • • • • • • • • • • • • • •	(II) Clarity	Complies
		(III) Free from embedded foreign particles and dust particles.	
		(IV) Free from cuts & Un filings.	
C	Physical Test	<u> </u>	
(a)	Syringe Barrel		
	faterial Polypropylene		Complies
	Grade	nde RP375R	
3	Total Height	86.50 mm ± 1.0 mm	Complies 85.79 mm - 85.80 mm
	Outer Diameter	6.50 mm ± 0.3 mm *	6.43 mm - 6.58 mm
	Inner Dimeter At Tip	2.40 mm ± 0.2 mm	2.24 mm - 2.42 mm
******	Outer Dimeter At Tip	5.10 mm ± 0.2 mm	4.95 mm - 5.10 mm
7	Flange Diameter	18.50 mm ± 0.3 mm	18.46 mm - 18.65 mm
8	Volume Marking	0.05ml, 0.06ml, 0.07ml, 0.08ml, 0.09ml, 0.1ml up to 1ml ±	10.40 mm - 10.03 mm
		10 %	Complies
(b)	Syringe Plunger		
	Material	High Density Polyethylene	Complies
		rade ACP 6541A	
	Total Height	92.50 mm ± 1.0 mm	Complies 92.38 mm - 92.65 mm
	Sucking Od	4.85 mm ± 0.2 mm	4.83 mm - 4.97 mm *
	Collar Diameter	15.00 mm ± 0.3 mm	15.05 mm - 15.19 mm
	Pouch		23.05 100 - 13.17 [[[]]
	Length Of Pouch	130.00 mm ± 10.0 mm	125 mm - 138 mm
<u>2 '</u>	Width Of Pouch	30.00 mm ± 5.0 mm	28 mm - 33 mm

Complies with our specification No. -BRV/FG-1903

Analyzed by:

Format No. FQC/021-06/00

్మరా Approved by: - (

ADDRESS: PLOT NO.15-16, S. NO. 66, NAIRPADA SAI PRABIAT UDYOG NAGAR-2 WALIV VASAI, PALGHAR, MAHARASHTRA 401208







CERTIFICATE OF ANALYSIS

Product: 1ml Dosing Syringe Product Code: SYPN01-WH - CE Batch/Lot No.: BRV240313 A.R. No.: FG-24-0698

MFG Date: 08/05/2024

Date: 10/05/2024 Batch/Lot size: 20,000 NOS Challan No.: EXP/2/2024-25 Exp Date: 3 Years from MFG,

Party's Name: Origin Packaging Ltd.

Sr. No	. Tests	Specification	Results
A	Description	1ml Dosing syringe marked at volume of 0.05ml, 0.06ml, 0.07ml, 0.08ml, 0.09ml up to 1ml with instruction (FOR ORAL USE ONLY) with individual BOPP sealing and CE0123 mark.	Complies
В	Appearance	Should confirm with (I) Colour Barrel: Natural (Markings in Black Ink) Plunger: WHITE (PL00075542) (II) Clarity (III) Free from embedded foreign particles and dust particles. (IV) Free from cuts & Un filings.	Complies
C	Physical Test		
(a)	Syringe Barrel		
1	Material	aterial Polypropylene Polypropylene	
2	Grade	RP375R	
3	Total Height	86.50 mm ± 1.0 mm	85.79 mm - 85.80 mm
	Outer Diameter	6.50 mm ± 0.3 mm	6.43 mm - 6.58 mm
	Inner Dimeter At Tip	2.40 mm ± 0.2 mm	2.24 mm - 2.42 mm
6	Outer Dimeter At Tip	5.10 mm ± 0.2 mm	4.95 mm - 5.10 mm
7	Flange Diameter	18.50 mm ± 0.3 mm	18.46 mm - 18.65 mm
	Volume Marking	0.05ml, 0.06ml, 0.07ml, 0.08ml, 0.09ml, 0.1ml up to 1ml ± 10 %	Complies
(b)	Syringe Plunger		
	Material	High Density Polyethylene	Complies
	Grade	ACP 6541A -	Complies
	Total Height	92.50 mm ± 1.0 mm	92.38 mm - 92.65 mm
	Sucking Od	4.85 mm ± 0.2 mm	4.83 mm - 4.97 mm
	Collar Diameter	15.00 mm ± 0.3 mm	15.05 mm - 15.19 mm
	Pouch		
	Length Of Pouch	130.00 mm ± 10.0 mm	125 mm - 138 mm
2	Width Of Pouch	30.00 mm ± 5.0 mm	28 mm - 33 mm

Complies with our specification No. -BRV/FG-1903

Analyzed by:

10/05/2024

Format No. FQC/021-06/00

Approved by:

Bharat Rubber Works Pvt. Ltd.

P